

4-WHEEL SCOOTER



OUTSTANDING
MANOEUVRABILITY,
OUTDOOR PERFORMANCE
AND LUXURY FEATURES

The **Apex Epic Mobility Scooter** offers the manoeuvrability of a 4-wheel mobility scooter along with high-performance features like 36 volts of power, full suspension and a hydraulic sealed brake system. The Apex Epic features style and a wealth of standard luxury touches including a wraparound delta tiller and LED lighting, making it the ultimate outdoor scooter.



PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

www.pride-mobilityscooters.co.uk

SPECIFICATIONS

APEX EPIC

4-wheel Model # MV714

Weight capacity:	28 Stone 8 lbs. (181 kg)
Maximum speed ¹ :	Up to 8 mph (12.87 km/h)
Ground clearance ² :	13.3 cm (5.25") at frame
Turning radius:	210.8 cm (83")
Overall length ² :	142 cm (56")
Overall width ² :	69.2 cm (27.25")
Front tyres:	10 cm x 33 cm (4" x 13") pneumatic
Rear tyres:	10 cm x 33 cm (4" x 13") pneumatic
Suspension:	Front and Rear
Total weight without batteries ⁵ :	123 kg (271 lbs.)
Heaviest piece when disassembled:	98 kg (216 lbs.)
Standard seating:	Type: Deluxe high-back seat with sliders Weight: 25 kg (55 lbs.) Material: Black Vinyl Dimensions: Width: 48 cm (19"), Depth: 43 cm (17")
Drive system:	Rear-wheel drive, sealed transaxle, 36-volt DC motor
Brakes:	Electro-magnetic with drum brake system
Battery requirements ³ :	(3) 12-volt, deep cycle Size: (3) 55 AH Weight: 17.24 kg (38 lbs.) each
Battery charger:	8-amp, 36V off-board

Color:



True Blue



Pearl White

FEATURES

- Full suspension for optimal handling
- Deluxe reclining high-back seat with headrest and sliders
- Enhanced tiller with wraparound handles and console
- Full LED-lighting package
- 36 volt battery system with (3) 12 volt 55 AH batteries
- Two rearview mirrors



Tiller with LED-lighting console

- ¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition. These specifications can be subject to a variance of (+/- 10%).
- ² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or 3%).
- ³ AGM or gel cell type required.
- ⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance test conducted at maximum weight capacity.
- ⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice.

The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.



Pride
Mobility Products Ltd.
— LIVE YOUR BEST —

PRIDE® MOBILITY SCOOTERS
LIVE YOUR BEST®

Tel. 0333 305 8274

www.pride-mobilityscooters.co.uk

admin@pride-mobilityscooters.co.uk



British
Healthcare
Trades
Association